

Tolomeo classic/classic LED
Tolomeo mini/mini LED
Tolomeo micro/micro LED
wall

design
Michele De Lucchi
Giancarlo Fassina
1987, 1991, 1996, 2006, 2010

Artemide®
www.artemide.net

Awards

Tolomeo parete
 Compasso d'Oro / A.D.I.
 1989 - Milano (Italia)

Wall mounted luminaires for adjustable direct task incandescent or LED lighting.

Materials: choice of: wall surface mounted bracket support \varnothing 3 1/4" (\varnothing 8.25 cm) in polished die-cast aluminum, suitable for luminaire cord and plug connection to wall outlet only • wall junction box or surface mounted bracket support \varnothing 4 1/2" (\varnothing 11.3 cm) in polished die-cast aluminum, suitable for dual installation • LED versions only suitable for plug-in application to wall outlet (cannot be hardwired to junction box as driver is on cord)

Light emission



Colors

Tolomeo classic

aluminum

black

white

polished aluminum

Tolomeo classic LED

aluminum

Tolomeo mini

aluminum

black

white

Tolomeo mini LED

aluminum

Tolomeo micro

aluminum

polished aluminum

Tolomeo micro LED


aluminum

Appliques murales à éclairage incandescent ou à DEL direct et ajustable.

Matériaux: selon le choix : support mural d'un diamètre de 3,25 po (8,25 cm) en aluminium moulé poli, convient au cordon d'alimentation de l'applique murale, nécessite un branchement que sur prise de courant murale • support en aluminium moulé poli, dont le diamètre est de 4,5 po (11,3 cm), pour une installation au moyen d'une boîte de connexion murale ou une installation en applique • les modèles à DEL ne peuvent être installés qu'au moyen d'une prise de courant murale (pas de raccordement fixe à la boîte de connexion étant donné que le circuit d'attaque est relié par cordon)

Luminarias de pared para iluminación incandescente o LED dirigida directa ajustable.

Materiales: opción de: soporte de pared de montaje superficial de \varnothing 3 1/4" (\varnothing 8,25 cm) de fundición de aluminio pulido, apto sólo para conectar cables de luminarias a tomacorrientes de pared • soporte de montaje superficial o caja de conexiones de pared de \varnothing 4 1/2" (\varnothing 11,3 cm) de fundición de aluminio pulido, apto para instalación doble • versiones LED sólo aptas para conexión en tomacorrientes de pared (no pueden conectarse directamente a cajas de conexiones, ya que el enchufe está en el cable)



Tolomeo classic/classic LED wall

incandescent source


• 1 x 100W (E26/A19)



or

LED source

• 5 LEDs/10W supplied



Tolomeo mini/mini LED wall

incandescent source


• 1 x 100W (E26/A19)



or

LED source

• 5 LEDs/10W supplied



Tolomeo micro/micro LED wall

incandescent source

• 1 x 60W (E26/G16 1/2)



or

LED source

• 4 LEDs/8W supplied



Tolomeo classic

Tolomeo mini



j-box bracket



surface bracket