

Tolomeo 7-10-12 wall shade

design



Michele De Lucchi
Giancarlo Fassina
2006

Artemide[®]
www.artemide.net

Light emission



Colors



Tolomeo 7 wall shade


incandescent source

- 1 x 60W (E26/A19)

or

fluorescent source

- 1 x 13W (GX24q-1/T4)



Tolomeo 10 wall shade


incandescent source

- 1 x 100W (E26/A19)

or

fluorescent source

- 1 x 18W (GX24q-2/T4)



Tolomeo 12 wall shade

incandescent source

- 1 x 150W (E26/A21)

or

fluorescent source

- 1 x 18W (GX24q-2/T4)



Adjustable wall mounted luminaires for direct and diffused incandescent or fluorescent lighting.

Materials: wall support, joints, canopy, and arm in polished aluminum • diffuser with aluminum frame in parchment paper or in pale grey satin and polycarbonate fiber blend • adjusts to full downward and max. 30° upward positions • mounting to standard electrical junction boxes • on/off switch on lampholder • newly redesigned to incorporate compact fluorescent option utilizing GU24 base with integrated ballast and lampholder

Appliques murales à éclairage incandescent ou fluorescent direct et diffus.

Matériaux: support mural, articulations, monture et bras en aluminium poli • diffuseur offert en papier parchemin ou en mélange de fibre de polycarbonate au fini gris pâle satiné, support en aluminium • s'ajuste pour adopter une position vers le bas complète ou encore une position vers le haut en inclinaison de 30° • se fixe aux boîtes de connexion électrique standard • interrupteur situé sur la douille de la lampe • modèle repensé compatible avec les ampoules fluorescentes compactes, base GU24 avec un ballast et douille de lampe intégrés

Luminarias de pared ajustables para iluminación incandescente o fluorescente directa y difusa.

Materiales: soporte de pared, articulaciones, cubierta y brazo de aluminio pulido • difusor con marco de aluminio, disponible en papel encerado o una combinación de satinado gris pálido y fibra de polycarbonato • se puede regular completamente hacia abajo o hasta 30° hacia arriba • montaje en cajas de conexiones estándar • interruptor de encendido/apagado en el portalámpara • nuevo diseño que incorpora una opción fluorescente compacta que utiliza la base GU24 con balasto y portalámpara integrados



Tolomeo 12

Tolomeo 10

Tolomeo 7

parchment